



MT500 Series Power Meter

- High performance imported optical detector
- Multifunctional integration (optical power meter, VFL, RJ45 cable test, flashlight)
- Low power consumption, continuous working for more than 80 hours
- Multi unit display dBm/dBmW
- Power saving function
- USB interface charging
- Ergonomic design, mini and small, easy to carry
- Support self calibration function

Items	Specifications
OPM	
Detector Type	InGaAs
Working Wavelength	800nm~1700nm
Display Resolution	0.01dBm
Frequency Identification	270Hz/330Hz/1kHz/2kHz
Optical Port	2.5mm universal FC/SC/ST
Self Calibration	Support
VFL	
Working Wavelength	650nm±30nm
Output Power	MT500-A2、MT500-B2、MT500-A2-C、MT500-B2-C: 2mW MT500-A10、MT500-B10、MT500-A10-C、MT500-B10-C: 10mW
Output Mode	CW/1Hz/2Hz
Optical Port	2.5mm universal FC/SC/ST
Others	
Battery (3 versions optional)	1) 3pcs AAA dry battery
	2) 3pcs AAA Ni-MH rechargeable battery
	3) Lithium battery
Data Storage	50 groups test data
TWIN Function	Auto wavelength recognition when working with FHS2 series laser source
Auto Power-off	10 minutes
Working Temp	-10℃~+50℃
Storage Temp	-25℃~+70℃
Humidity	0~95% (No condensation)
Dimension	104L×67W×28Hmm
Weight	140g

Model	USB Charge	Test Range	Calibrated Wavelength	Accuracy
MT500-A2, MT500-A10	Not support	-70dBm~+6dBm	850/1300/1310/1490/1550/1625 /1650nm	±0.35dB
MT500-A2-C, MT500-A10-C	support			
MT500-B2, MT500-B10	Not support	-50dBm~+26dBm		
MT500-B2-C, MT500-B10-C	support			