



No Bluetooth

FHP2G10 Selective Power Meter

- Support selective power level 1490nm/1577nm measurements separately at the same time
- Applicable to GPON&XG(S)-PON and EPON&10G-EPON co-existence PON network
- Normal broadband power meter support 1270nm/1310nm/1550nm/1625nm
- Built in 10mw VFL function
- 10 groups User defined Pass, Warning, Fail mode
- Support USB Type-C charging and test data upload
- Support Powerful PC software to generate the test report
- Bluetooth is optional

Items	Specifications
Optical Port	OPM: SC/UPC or SC/APC
	VFL:SC/UPC
Selective Power Measure	1490nm/1577nm
Calibrated Wavelength	Broadband channel 1: 1270nm/1310nm/1490nm
	Broadband channel 2: 1550nm/1577nm/1625nm
Test Range	-40~+10dBm
Test Accuracy	±0.5dB
Resolution	0.01
Display Unit	dBm/dB/mw
Isolation	1490nm>35dB; 1577nm>35dB
VFL	10mW, CW / 2Hz
Memory Capacity	999groups
Threshold Setting	10groups(Pre-set by PC software)
Communication Port	Type-C USB port
Bluetooth	Optional
Power Supply	2*2500mAh Ni-MH AA battery
External Power Supply	5V/1A AC/DC adapter
Working Temp	-10°C~+50°C
Storage Temp	-20°C~+70°C
Dimension	160L×76W×45H(mm)
Weight	300g