FHS2 Series Laser Source

- Both single mode and multiple mode laser are available
- With FHP2 series power meter, automatic wavelength identification can be realized
- Stable output laser, rugged and portable
- Auto power-off and backlight function
- Support CW, 270Hz, 330Hz, 1kHz and 2kHz mode output

Items		Specifications				
		FHS2D02	FHS2D02F	FHS2T01F	FHS2Q01F	FHS2Q02F
Wavelength	1310/1550nm	√	√			
	1310/1490/1550nm			√		
	850/1300/1310/1550nm				√	
	1310/1550/1490/1625nm					√
Others	Spectral Width	5nm				
	Output Power	-5dBm(Typical)				
	Output Adjustable Range	±3dB	-	-	-	-
	270/1k/2kHz output frequency	√	√	√	√	√
	Auto wavelength recognition	√	√	√	√	√

Laser type	FP-LD
Output Stability	Short Term (15minutes): <0.05dB
	Long Term (8 hours or above): <0.1dB
Power Supply	2*Ni-MH AA battery
Working Temp	-10℃~+50℃
Storage Temp	-20℃~+70℃
Dimension/Weight	160L×76W×45H(mm) / 260g
Accessories	2*Ni-MH AA battery, FC adapter, SC adapter, 3*ceramic sleeves,Power adapter, USB cable, Test report, Quick guide, Carrying bag
Customization	FC/APC, SC/APC, ST/APC

Let's go in the grandway!