



FIM-3 Fiber Microscope

- Convenient using both for male and female adapters
- Widely used in PON, CWDM, DWDM, SDH, SONET etc.
- Magnification: 250* via 3.5" TFT LCD; 400* via 8" TFT LCD
- Through the USB 2.0 interface, the PC software can be connected to analyse and record the test results(Optional function)

Items	Specifications
Magnification	400x (8" Monitor), 250x (3.5" Monitor)
Resolution	0.5μm
Display Screen	3.5" TFT-LCD, 320x240 pixels
	8" TFT-LCD, 1024x768 pixels
Video Output	NTSC/PAL
Power Supply	3.7V 4500mA / 5V 1A Li-Battery
Working Temp	-20°C~+50°C
Storage Temp	-30°C~+60°C
Weight	1.5kg

Standard Accessories:

Inspection Probe x1	3.5" monitor x1	25-U-M x1
125-U-M x1	FC-PC-F x1	SC-PC-F x1
LC-U-F x1	Recharger	Manual
Carrying bag	Li Battery	

Optional Accessories:

25-A-M	125-A-M	SC-A-F
FC-A-F	AV-USB 2.0 Converter	

Applications

Tips Type	Function Description
25-U-M	FC/SC/ST/E2000 patch cord UPC connector
125-U-M	LC/MU patch cord UPC connector
25-A-M	FC/SC/ST/E2000 patch cord APC connector
125-A-M	LC/MU patch cord APC connector
FC-PC-F	FC UPC bulkhead
SC-PC-F	SC UPC bulkhead
LC-U-F	LC UPC bulkhead
SC-A-F	SC APC bulkhead
FC-A-F	FC APC bulkhead

Let's go in me grandway!

