



OFI-6 Optical Fiber Identifier

- Continuously detecting the presence and directional frequency of fiber optic signals under business conditions
- Low insertion loss, does not affect online business
- Universal testing adapter, suitable for 250um bare fiber, 0.9mm/2mm/3mm patchcord
- Exquisite and compact, suitable for one handed operation, easy to grip
- Equipped with power meter and VFL function
- LED lighting function
- Type-C charging interface

Items	Specifications
Fiber Identifier	
Detector Type	2pcs 1mm InGaAs
Working Wavelength	800nm~1700nm
Test Range	-40~+10dBm
Insertion Loss	<2dB(1550nm); <1dB(1310nm)
Application Of Optical Fiber	Universal adapter for 250um/900um/2mm/3mm optical fiber
Identified Signal Type	CW/270Hz/330Hz/1kHz/2kHz
Online Power Measurement	Yes
Online Power Direction	Left or right
OPM	
Working Wavelength	800~1700nm
Calibrated Wavelength	850/1300/1310/1490/1550/1625/1650nm
Measurement Range	-70~+6dBm or -50~+26dBm
Optical Port	2.5mm universal connector
VFL	
Working Wavelength	650nm±10nm
Output Power	10mw; CW/1Hz/2Hz
Optical Port	2.5mm universal connector
Others	
Power Supply	Two No. 5 dry batteries or 1000mAh lithium batteries
USB Port	Type-C
Working Temp	-10℃~+50℃
Storage Temp	-20℃~+70℃